Manual Autoclaves M/MK

Tuttnauer manual autoclaves will compliment any healthcare facility and satisfy all of your sterilization needs. The bright, new, easy to use panel was designed with the operator in mind. Time tested reliability and durability are built into every Tuttnauer product.

FEATURES:

- Automatic shut off at the end of both the sterilization and dry cycles.
- A long life electro polished chamber and door.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir.
- Dual safety thermostat to protect against overheating.
- International certifications.
- 1 year parts and labor warranty.



M Series

ltem No.	Chamber Dimensions Ø x L in(mm)	Volume	Overall Dimensions DxWxH in(mm)	Standard Cassette Capacity	Tray Dimensions DxWxH in(mm)	No. of Trays	Standard Unwrapped Cycle Time	Voltage(V) Freq.(Hz)	Power(W) Current(A)	Shipping Weight Ibs(kg)
2340M	9" x 18"	5gal/19L	21.5"x20"x14.4"	2 full and 2 half	16.3"x6.7"x0.8"	3	Cold: 27 mins	120V	1400W	85
	(230 x 470)		(545x510x365)		(415x170x20)		Hot: 13 mins	50/60	12A	(39)
2540M	10" x 19"	6gal/23L	21.5"x20"x14.4"	3 full and 3 half	16.3"x6.7"x0.8"	4	Cold: 30 mins	120V	1400W	85
	(254 x 475)		(545x510x365)		(415x170x20)		Hot: 14 mins	50/60	12A	(39)

Manual Kwiklave[™] MK Series

2540MK	10" x 19"	6gal/23L	21.5"x20"x14.4"	3 full and 3 half	16.3"x6.7"x0.8"	4	Cold: 21 mins	230V	2200W	85
	(254 x 475)		(545x510x365)		(415x170x20)	4	Hot: 11 mins	50/60	10A	(39)

The Tuttnauer M Series is also available in a quick cycle model, the Kwiklave (MK). This sterilizer offers all the proven, dependable features of our manual autoclave, with the added benefit of reducing the total heat up time. This autoclave is the perfect choice for quick instrument turnaround or a high volume office. Speed and reliability are accomplished without sacrificing load size. 1 year parts and labor warranty.

Large Capacity Manual Autoclave

Our largest manual tabletop autoclave. Perfect for multi-doctor practices, clinics or surgery centers. 15" x 30" chamber accommodates longer instruments or a large number of small instruments. Capacity for 15 full size IMS cassettes. 1 year parts and labor warranty. Model 2540MK requires a voltage between 220V and 235V for proper operation. When applicable a buck/boost transformer (0.5KVA) may be required.

2 Timer 3 Thermostat



ltem No.	Chamber Dimensions Ø x L in(mm)	Volume	Overall Dimensions DxWxH in(mm)	Standard Cassette Capacity	Tray Dimensions DxWxH in(mm)	-	Standard Unwrapped Cycle Time	Voltage(V) Freq.(Hz)	Power(W) Current(A)	Shipping Weight Ibs(kg)
3870M	15" x 30"	22gal/85L	34.5"x26"x20.6"	15 full	26.6"x11.3"x1"	2	Cold: 32 mins	230V	3000W	209
	(384 x 760)		(875x665x525)		(675x286x25)		Hot: 23 mins	50/60	13.6A	(95)
					26.6"x13.8"x1"					
					(675x350x25)					

All published cycle times are estimated. Actual times may vary depending on load size and voltage.