

Thoracic Drainage Aspirator Model 6020



The Gomco 6020 is a mobile aspirator which is specialized for thoracic drainage for hospitals. It generates up to -25 cm H₂O of vacuum pressure with a 2.3 lpm flow rate at open flow.

Key Features

- Silent operation due to a Gomco exclusive thermotic pump design
- Water seal in the collection bottle prevents aspirated air from re-entering the chest
- Easy-to-store and transport compact design with a flat stainless steel top
- Convenient storage for 6' electrical cord with hospital-grade plug
- Disposable hydrophobic bacteria filter helps prevent fluid and aerosol contamination

Specifications

Vacuum Range:	0 to -25 cm H ₂ O (0 to -18.4 mm Hg)
Flow Rate:	2.3 lpm (minimum) at open flow
Sound Level:	Less than 47 dBA
Pump Type:	Thermotic
Electrical Cord:	6' hospital grade
Dimensions:	18" W x 17" D x 33" H (46 x 43 x 84 cm)
Weight:	52 lbs. (24 kg)
UL/ETL Listed:	Yes
Warranty:	1 year

Model	Voltage	Poly Bottle
01-32-6020	115V/50-60 Hz	1 - 2800 ml
01-73-6020	220V/50-60 Hz	1 - 2800 ml

All models come with disposable suction tubing and 3 disposable hydrophobic bacteria filters.

01-90-2000	Disposable Suction Tubing Kit, one 18" & one 72" per pkg.
01-90-3694	Polycarbonate Collection Bottle, with metal cover and cap & float assembly, 2800 ml



EMERGO EUROPE
Prinsessegracht 20
2514 AP, The Hague
The Netherlands

01-73-6020



MADE IN USA



Allied Healthcare Products, Inc. • 1720 Sublette Avenue • St. Louis, MO 63110 USA
314/771-2400 • 800/444-3954 • FAX: 314/771-0650 • www.alliedhpi.com

U.S.
Toll Free: 800/444-3940
FAX: 800/477-7701

Canada & Mexico
Toll Free: 800/446-0552
FAX: 800/246-6201

International
Telephone: 314/268-1683
FAX: 314/771-5183

ISO 13485: 2003

©Allied Healthcare Products, Inc.®

All specifications are nominal and subject to change without notice.

Form 21-00-6020
July 2013