



2500 PalmSAT[®] Series

Digital Handheld
Pulse Oximetry

Proven Performance in Real World Applications

PalmSAT – the next generation in handheld pulse oximetry – small, yet versatile digital pulse oximeters designed to accurately assess oxygen saturation and pulse rate. The compact size, ease of operation, and choice of alarm or non-alarm versions make the PalmSAT series ideal for your portable monitoring needs – regardless of the patient's location.



Product Highlights

- ✓ Choice - Alarm & non-alarm versions
- ✓ Simple - Easy two-button operation
- ✓ Compact Size - 7.5 oz. unit for easy handling
- ✓ Flexible - AA batteries, rechargeable batteries, or AC power with charger stand
- ✓ Powerful - Memory for 72 hours of data storage
- ✓ Efficient - 2500: 100 hrs of battery life:
45 hrs - rechargeable batteries 2500A: 60 hrs of
battery life: 40 hrs - rechargeable batteries

✓ Where People Make the Difference



Versatility

Nonin has combined advanced technology and algorithms based on years of invaluable clinical experience to provide a wide range of functions. The functionality of the PalmSAT 2500 Series also makes it useful for an array of medical locations and applications including:

| | |
|-----------------------|---|
| ✓ Hospitals | ✓ Emergency Services |
| ✓ Pre & Post Op | ✓ Transport |
| ✓ Procedure Rooms | ✓ Nursing Homes |
| ✓ Urgent Care | ✓ Sleep Studies - basic overnight screening |
| ✓ Physician's Offices | ✓ Dental & Oral Surgery |
| ✓ Same Day Surgery | |

Nonin's optional Windows®-based software package, nVISION®, permits the seamless transfer of all stored data from 72 hours of memory to a PC for further analysis, comprehensive report generation, and storage.

Pure Functionality

| | 2500 Non-Alarm | 2500A Alarm |
|--------------------------------|---|---|
| |  |  |
| Battery Life | 100 hrs | 60 hrs |
| NiMH rechargeable battery pack | 45 hrs | 40 hrs |
| Memory | 72 hrs | 72 hrs |
| Alarm Functions | | |
| Audible | | ✓ |
| Visible | | ✓ |
| Pulse Rate High/Low | | ✓ |
| SpO ₂ High/Low | | ✓ |
| Low Perfusion | | ✓ |

Features

| | | |
|--------------------------------|---------|--------|
| Battery Life | 100 hrs | 60 hrs |
| NiMH rechargeable battery pack | 45 hrs | 40 hrs |
| Memory | 72 hrs | 72 hrs |

Alarm Functions

| | | |
|---------------------------|--|---|
| Audible | | ✓ |
| Visible | | ✓ |
| Pulse Rate High/Low | | ✓ |
| SpO ₂ High/Low | | ✓ |
| Low Perfusion | | ✓ |

Select Your Options



Carrying Case

Many options allow you to customize the PalmSAT 2500 series to meet your application needs.

- ✓ PureLight® Sensors
- ✓ PalmSAT Charger Stand and NiMH Battery Pack
- ✓ nVISION Data Management Software
- ✓ PC Interface Cable
- ✓ Carrying Case

Please contact your authorized distributor for more information.

Specifications

Oximeter

| | |
|--|-----------------------------|
| Oxygen Saturation Range (%SpO ₂) | 0% to 100% |
| Pulse Rate Range | 18 to 300 pulses per minute |
| Displays | |
| Pulse Quality | LED, tri-color |
| Alarm Indicator | LED, bi-color |
| Alarm Silenced | LED, yellow |
| Numeric Displays | 3-digit 7-segment LEDs, red |
| Low Battery | LED, yellow |

Accuracy*

| | |
|---|----------------------|
| Blood Oxygen Saturation (%SpO ₂) (±1 S.D.) ^b | |
| No Motion: Adults, Pediatrics | 70 - 100% ± 2 digits |
| Neonates | 70 - 100% ± 3 digits |
| Motion: Adults, Pediatrics | 70 - 100% ± 3 digits |
| Neonates | 70 - 100% ± 4 digits |
| Low Perfusion: Adults, Pediatrics | 70 - 100% ± 3 digits |
| Neonates | 70 - 100% ± 4 digits |

Pulse Rate:

| | |
|----------------|-------------------------|
| No Motion: | 18 - 300 bpm ± 3 digits |
| Motion: | 40 - 240 bpm ± 5 digits |
| Low Perfusion: | 40 - 240 bpm ± 3 digits |

Temperature

| | |
|------------------------|--------------------------------|
| Operating | -4° to +122°F (-20° to +50°C) |
| Storage/Transportation | -22° to +122°F (-30° to +50°C) |

Humidity

| | |
|------------------------|--------------------------|
| Operating | 10% to 90% noncondensing |
| Storage/Transportation | 10% to 95% noncondensing |

Altitude

| | |
|---------------------|-----------------------------------|
| Operating Altitude | Up to 40,000 feet (12,000 meters) |
| Hyperbaric Pressure | Up to 4 atmospheres |

Power Options

| | |
|--------|---|
| 2500: | Four 1.5 V AA size alkaline batteries (100 hours typical operation) NiMH rechargeable battery pack (45 hours typical operation) AC power (charging stand) |
| 2500A: | Four 1.5 V AA size alkaline batteries (60 hours typical operation) NiMH rechargeable battery pack (40 hours typical operation) AC power (charging stand) |

Weight

| | |
|--------|--|
| 2500: | 7.4 oz (210 g) with alkaline batteries 8.1 oz (230 g) with NiMH batteries |
| 2500A: | 7.5 oz (213 g) with alkaline batteries 8.2 oz (233 g) with NiMH batteries |

Dimensions

| | |
|------------|---|
| Dimensions | 1.3 x 2.8 x 5.4 in. (3.2 x 7.0 x 13.8 cm) |
|------------|---|

Warranty

| | |
|----------|---------|
| Warranty | 3 years |
|----------|---------|

Classifications per IEC 60601-1

| | |
|----------------------|----------------------|
| Degree of Protection | Type BF-Applied Part |
|----------------------|----------------------|

*Accuracy is expressed for adult patients and determined with the Reusable 8000AA Finger Clip Sensor. All accuracy specifications are results determined by induced hypoxia studies on healthy adult volunteers. Motion accuracy specifications apply to the 8000AA Finger Clip Sensor. Accuracy specifications may vary with use of other sensor types indicated for use with the 2500 series. Refer to your Operator's Manual for details.

^bS.D. (Standard Deviation) is a statistical measure; up to 32% of the readings may fall outside these limits.

Quality Systems registered to ISO 13485:2003 and EC certificate per Annex II, clause 3 of EC Directive No. 93/42/EEC concerning medical devices.



Specifications are subject to change without notice.

Your Partner of Choice



With over 18 years of experience and dedication to the design and support of noninvasive monitoring devices, Nonin has helped many medical professionals meet clinical and economic objectives. Trusted by clinicians worldwide, countless tests are performed every day on thousands of Nonin pulse oximeters in more than 125 countries. Nonin's dedication to technological leadership, precision manufacturing and uncompromised customer support ensures quality products and service you expect.



www.nonin.com

Nonin Medical, Inc.
13700 1st Avenue North
Plymouth, MN 55441-5443, USA
Phone: +1.763.553.9968 Toll Free: 1.800.356.8874
Fax: +1.763.553.7807
info@nonin.com

✓ Where People Make the Difference