

Valueklave™ 1730

Tuttnauer™
Your Sterilization & Infection Control Partners



Speed, Quality and Value

- Fast cycle time, 11 minutes from a hot start (Standard Unwrapped Cycle Time)
- Efficient drying cycle for wrapped instruments
- Contemporary design with easy to read panel
- Economically priced in a compact size



Valueklave™ 1730

The Valueklave™ 1730 will satisfy all of your basic sterilization needs at an economical price. High speed and reliability are built into every Valueklave™ 1730.



Valueklave™ 1730 Specifications

Chamber Dimensions Ø x L In (mm)	7"x13" (170 x 340)
Volume	2 gal/7.5L
Overall Dimensions DxWxH In (mm)	17.9"x17.4"x12" (455 x 440 x 305)
Standard Cassettes	2 half
Tray Dimensions DxWxH In (mm)	11.6"x4.7"x 0.8" (295 x 120 x 20)
No. of Trays	3
Standard Unwrapped Cycle Time	Cold: 16 mins Hot: 11 mins
Voltage (V)	120
Freq. (Hz)	50/60
Power (W)	1350
Current (A)	11
Shipping Weight lbs (kg)	55 (25)

Features:

- Fast Cycle Time. 11 minutes from a hot start* (Standard Unwrapped Cycle time).
- Automatic shut off at the end of both the sterilization and dry cycles.
- A long life electro polished chamber and door.
- Double safety locking device prevents door from opening while chamber is pressurized.
- Overheat cutoff prevents burnout of heating elements in case of insufficient water in the chamber.
- Drain valve is located on the front, allowing for quick and easy draining of water reservoir.
- Dual safety thermostat to protect against overheating.
- International certifications.



YZK

LTR330-0005 / NALF / USA / N-2 / 07.09



Chamber Brite™
Autoclave Cleaner



Clean & Simple™ Ultrasonic Cleaners



Clean & Simple™ Tablets



Steam Distiller Model 9000™

Tuttnauer USA Co., Ltd. 25 Power Drive, Hauppauge, NY 11788
Tel: (800) 624 5836, (631) 737 4850, Fax: (631) 737 0720
Email: info@tuttnauerUSA.com, www.tuttnauerUSA.com

Tuttnauer™
Your Sterilization & Infection Control Partners